

Overview

Models

HP 1905-24 Switch	JD990A
HP 1905-48 Switch	JD994A
HP 1905-24-PoE Switch	JD992A
HP 1905-8-PoE Switch	JD877A

Key features

- Customized operation using intuitive Web interface
- Fast Ethernet Layer 2 operation
- Access control lists for enhanced security
- Spanning Tree: STP and RSTP
- 3-year warranty

Product overview

HP 1905 Switch Series devices are smart managed fixed-configuration Fast Ethernet Layer 2 switches designed for small businesses looking for key features in an easy-to-administer, low-cost solution. Fast Ethernet models include: 24- and 48-port non-PoE switches, 8- and 24-port PoE Fast Ethernet switches. Also available is a 10-port PoE Gigabit Ethernet switch. These smart managed switches come preconfigured for fast and easy installation, yet allow network operation to be enhanced using an intuitive Web-based management interface. Advanced security and quality of service features create a voice-ready network. HP 1905 series switches are solidly built for business operation, and are designed for high reliability, long life, low power consumption, and low total cost of ownership. The HP 1905 switches come with a 3-year warranty, covering unit, fans, and power adapters or power supplies.

Features and benefits

Quality of Service (QoS)

- **Traffic prioritization** (IEEE 802.1p): allows real-time traffic classification mapped to four hardware queues per port

Management

- **Simple Web management:** Intuitive Web GUI allows for easy management of device by even nontechnical users
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **SNMPv1, v2c:** devices can be discovered and monitored from an SNMP management station
- **Port mirroring:** allows traffic to be mirrored on any port or a network analyzer to assist with diagnostics or detecting network attacks
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol for easy mapping by network management applications

Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all ports
- **Front-panel LEDs:** provide an at-a-glance view of status, activity, speed, and full-duplex operation
- **Flow control:** helps ensure reliable communications during full-duplex operation
- **Small Form-Factor Pluggable (SFP) slots:** allow for fiber connectivity
- **Cable diagnostics:** remotely detect cable issues using a browser-based tool

Overview

Performance

- **Link aggregation** (trunking): groups together up to eight links per trunk to increase bandwidth and create redundant connections
- **IGMP snooping**: multicast filtering improves network performance, instead of flooding traffic to all ports

Layer 2 switching

- **VLAN support and tagging**: support up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups
- **Spanning Tree** (STP/RSTP): prevents network loop

Security

- **Access control lists** (ACLs): allow network managers to define classification actions and rules for specific ingress ports
- **Secure Sockets Layer** (SSL): encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X**: utilizes an industry-standard user authentication with an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server

Convergence

- **Auto Voice VLAN**: recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones
- **IEEE 802.3af Power over Ethernet** (1905-24-PoE): provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras (see product specifications for total PoE power available)

Additional information

- **Green initiative support**: provides support for RoHS and WEEE regulations

Warranty and support

- **3-year warranty**: with advance replacement and next-business-day delivery (available in most countries)
- **Electronic and telephone support**: limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**: to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Technical Specifications

HP 1905-24 Switch (JD990A)

Ports	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full	
	2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)	
	1 RJ-45 serial console port	
Physical characteristics	Dimensions	17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height)
	Weight	6.8 lb (3.08 kg)
Memory and processor	Processor	ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 KB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μ s
	1000 Mb Latency	< 5 μ s
	Throughput	6.6 million pps
	Routing/Switching capacity	8.8 Gbps
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, non-condensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	10% to 95%, non-condensing
	Acoustic	Fanless
Electrical characteristics	Voltage	100-240 VAC
	Frequency	50/60 Hz
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	
Management	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	
Notes	The HP 1905-24 Switch (JD990A) was formerly sold as the 3Com Baseline Plus 2226 (3CBLSF26H) and may ship with this product labeling.	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E)	
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW021E)	
	3-year, 24x7 SW phone support, software updates (UV795E)	
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)	
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)	
	4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E)	
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E)	

Technical Specifications

4-year, 24x7 SW phone support, software updates (UV796E)
 5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E)
 5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E)
 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E)
 5-year, 24x7 SW phone support, software updates (UV797E)
 3 Yr 6 hr Call-to-Repair Onsite (UW018E)
 4 Yr 6 hr Call-to-Repair Onsite (UW019E)
 5 Yr 6 hr Call-to-Repair Onsite (UW020E)
 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)
 1-year, 24x7 software phone support, software updates (HR685E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1905-48 Switch (JD994A)

Ports	48 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full	
	2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)	
	1 RJ-45 serial console port	
Physical characteristics	Dimensions	17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height)
	Weight	6.4 lb (2.9 kg)
Memory and processor	Processor	ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	
Performance	100 Mb Latency	< 5 μ s
	1000 Mb Latency	< 5 μ s
	Throughput	10.1 million pps
	Routing/Switching capacity	13.6 Gbps
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, non-condensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	10% to 95%, non-condensing
	Acoustic	Fanless
Electrical characteristics	Voltage	100-240 VAC
	Frequency	50/60 Hz
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	

Technical Specifications

Management	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	The HP 1905-48 Switch (JD994A) was formerly sold as the 3Com Baseline Plus 2250 (3CBLSF50H) and may ship with this product labeling.
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW021E)</p> <p>3-year, 24x7 SW phone support, software updates (UV795E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E)</p> <p>4-year, 24x7 SW phone support, software updates (UV796E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E)</p> <p>5-year, 24x7 SW phone support, software updates (UV797E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW018E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW019E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW020E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 24x7 software phone support, software updates (HR685E)</p>

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1905-24-PoE Switch (JD992A)

Ports	24 RJ-45 autosensing 10/100 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3af PoE); Media Type: Auto-MDIX; Duplex: half or full
	2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)
	1 RJ-45 serial console port
Physical characteristics	<p>Dimensions 17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height)</p> <p>Weight 7.1 lb (3.22 kg)</p>
Memory and processor	Processor ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
Performance	<p>100 Mb Latency < 5 μs</p> <p>1000 Mb Latency < 5 μs</p> <p>Throughput 6.6 million pps</p> <p>Routing/Switching capacity 8.8 Gbps</p>
Environment	Operating temperature 32°F to 113°F (0°C to 45°C)

Technical Specifications

Operating relative humidity	10% to 90%, non-condensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	10% to 95%, non-condensing

Electrical characteristics	Voltage	100-240 VAC
	Frequency	50/60 Hz

Safety UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03

Emissions FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A

Management limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB

Notes The HP 1905-24-PoE Switch (JD992A) was formerly sold as the 3Com Baseline Plus 2426 PWR (3CBLSF26PWRH) and may ship with this product labeling.

Services

- 3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW021E)
- 3-year, 24x7 SW phone support, software updates (UV795E)
- 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E)
- 4-year, 24x7 SW phone support, software updates (UV796E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E)
- 5-year, 24x7 SW phone support, software updates (UV797E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW018E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW019E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW020E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)
- 1-year, 24x7 software phone support, software updates (HR685E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1905-8-PoE Switch (JD877A)

Ports 8 RJ-45 autosensing 10/100 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3af PoE); Media Type: Auto-MDIX; Duplex: half or full

1 RJ-45 dual-personality 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)

Technical Specifications

	1 RJ-45 serial console port
Physical characteristics	Dimensions 13.0(w) x 8.0(d) x 1.7(h) in (33.02 x 20.32 x 4.32 cm) (1U height)
	Weight 4.5 lb (2.04 kg)
Memory and processor	Processor BCM 53202 @ 133 MHz, 32 MB SDRAM, 8 MB flash; packet buffer size: 1 MB
Mounting	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
Performance	100 Mb Latency < 5 μ s
	1000 Mb Latency < 5 μ s
	Throughput 2.7 million pps
	Routing/Switching capacity 3.6 Gbps
Environment	Operating temperature 32°F to 113°F (0°C to 45°C)
	Operating relative humidity 10% to 90%, non-condensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 10% to 95%, non-condensing
	Acoustic Fanless
Electrical characteristics	Voltage 100-240 VAC
	Frequency 50/60 Hz
Safety	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
Management	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
Notes	The HP 1905-8-PoE Switch (JD877A) was formerly sold as the 3Com OfficeConnect Managed Fast Ethernet PoE Switch (3CRDSF9PWR) and may ship with this product labeling.
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW488E) 3-year, 24x7 SW phone support, software updates (UV789E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E) Installation with minimum configuration, system-based pricing (UW451E) Installation with minimum configuration, system-based pricing (UY901E) Installation with HP-provided configuration, system-based pricing (UY902E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E) 4-year, 24x7 SW phone support, software updates (UV790E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone(UW490E)

Technical Specifications

5-year, 24x7 SW phone support, software updates (UV791E)
3 Yr 6 hr Call-to-Repair Onsite (UW491E)
4 Yr 6 hr Call-to-Repair Onsite (UW492E)
5 Yr 6 hr Call-to-Repair Onsite (UW493E)
1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)
1-year, 24x7 software phone support, software updates (HR685E)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols
(applies to all products in series)

Device management

RFC 2819 RMON

General protocols

IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.3ab 1000BASE-T
IEEE 802.3ac (VLAN Tagging Extension)
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3i 10BASE-T
IEEE 802.3u 100BASE-X
IEEE 802.3x Flow Control
IEEE 802.3z 1000BASE-X

MIBs

RFC 1213 MIB II
RFC 1493 Bridge MIB
RFC 2021 RMONv2 MIB
RFC 2233 Interface MIB
RFC 2233 Interfaces MIB
RFC 2571 SNMP Framework MIB
RFC 2572 SNMP-MPD MIB
RFC 2573 SNMP-Notification MIB
RFC 2573 SNMP-Target MIB
RFC 2613 SMON MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2667 IP Tunnel MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 3414 SNMP-User based-SM MIB
RFC 3415 SNMP-View based-ACM MIB
RFC 3418 MIB for SNMPv3

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
IEEE 802.1D (STP)
RFC 1215 SNMP Generic traps

QoS/CoS

Technical Specifications

IEEE 802.1P (CoS)

Security

IEEE 802.1X Port Based Network Access Control

Accessories

HP 1905 Switch Series accessories

Transceivers

HP X124 1G SFP LC SX Transceiver	JD493A
HP X120 1G SFP LC LX Transceiver	JD119B
HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X124 1G SFP LC LX Transceiver	JD494A

Cables

HP .5m Multi-mode OM3 LC/LC Optical Cable	AJ833A
HP 1m Multi-mode OM3 LC/LC Optical Cable	AJ834A
HP 2m Multi-mode OM3 LC/LC Optical Cable	AJ835A
HP 5m Multi-mode OM3 LC/LC Optical Cable	AJ836A
HP 15m Multi-mode OM3 LC/LC Optical Cable	AJ837A
HP 30m Multi-mode OM3 LC/LC Optical Cable	AJ838A
HP 50m Multi-mode OM3 LC/LC Optical Cable	AJ839A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
NEW HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP X124 1G SFP LC SX Transceiver (JD493A) JD493A HP X124 1G SFP LC SX Transceiver that provides a full duplex Gigabit solution up to 550m on Multi Mode fiber.	Ports	1 LC 1000BASE-SX port	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	850 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1 W
	Cabling	Maximum distance: • 220m-550m	
	Services	Fiber type	Multi Mode
		Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP X120 1G SFP LC LX Transceiver (JD119B) A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF	Ports	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	1300 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type: Either single mode or multimode;	
		Maximum distance: • 550m for Multimode • 10km for Singlemode	
	Services	Fiber type	Both
Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

Accessory Product Details

<p>HP X121 1G SFP LC SX Transceiver (J4858C)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.</p>	<p>Ports</p> <p>1 LC 1000BASE-SX port; Duplex: full only</p> <p>Physical characteristics</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm) Weight: 0.04 lb. (0.02 kg) Transceiver form factor: SFP</p> <p>Environment</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 5% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)</p> <p>Electrical characteristics</p> <p>Power consumption typical: 0.4 W Power consumption maximum: 0.7 W</p> <p>Cabling</p> <p>Type:</p> <ul style="list-style-type: none"> ● 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; <p>Maximum distance:</p> <ul style="list-style-type: none"> ● 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth) ● 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth) ● 2-500 m (50 µm core diameter, 400 MHz*km bandwidth) ● 2-550 m (50 µm core diameter, 500 MHz*km bandwidth) <p>Cable length: 2-550m Fiber type: Multi Mode</p> <p>Services</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
--	---

<p>HP X121 1G SFP LC LX Transceiver (J4859C)</p> <p>HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.</p>	<p>Ports</p> <p>1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only</p> <p>Physical characteristics</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)</p> <p>Environment</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)</p> <p>Cabling</p> <p>Type:</p> <ul style="list-style-type: none"> ● Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; <p>Maximum distance:</p> <ul style="list-style-type: none"> ● 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth) ● 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth) ● 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth) ● 2-10,000 m (single-mode fiber)
--	--

Accessory Product Details

Notes	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X124 1G SFP LC LX Transceiver (JD494A)

A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF

Ports	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)
Connectivity	Connector type LC
	Wavelength 1300 nm
Physical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight 0.04 lb. (0.02 kg)
	Transceiver form factor SFP
Electrical characteristics	Power consumption typical 0.8 W
	Power consumption maximum 1.0 W
Cabling	Maximum distance: • 500m for Multimode • 10km for Singlemode
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cabling	Cable type: 50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m
	Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m
Notes	Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end. <ul style="list-style-type: none"> • Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm • Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm. • Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links. • CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.

Accessory Product Details

- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 2 m Multimode OM3 LC/LC Optical Cable
(AJ835A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 5 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ836A)

Cable type:

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 15 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ837A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 30 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ838A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 50 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ839A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
1m Cable (QK732A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
2m Cable (QK733A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.