

LTO[®]-4 HH SAS TAPE DRIVE

High Capacity, Half-Height Tape Drive



FEATURES + BENEFITS

Network Flexibility

6 Gb/s SAS interface can connect to a range of open system servers

High Data Transfer Rates

Native data transfer rates of up to 120 MB/sec

Intelligent Operation

Internal data buffer helps improve access rates and reduce cartridge fill and rewind times

Backward Compatibility

Can read and write to LTO Ultrium 4 tape cartridges and LTO Ultrium 3 cartridges; can read LTO Ultrium 2 cartridges

Information Security

Secure storage available through LTO Ultrium 4 data encryption standard

PERFORMANCE AND VERSATILITY

The Imation LTO-4 HH SAS Tape Drive helps you handle increasing demands for data storage while maintaining efficient backup times. Built to meet all specifications of the fourth-generation Linear Tape-Open (LTO) standard, the Imation LTO-4 HH SAS Tape Drive is designed for businesses that need affordable archival data storage or make regular backups. It provides up to 6 Gb/s Serial Attached SCSI (SAS) connectivity and the security of LTO-based data encryption.

Featuring a half-height form factor, the Imation LTO-4 HH SAS Tape Drive offers up to 800 GB of native data capacity in conjunction with Imation Ultrium tape cartridges and up to 1.6 TB with 2:1 software compression. Data transfer rates of up to 120 MB/sec. allow fast and efficient backup and archiving operations. This format provides a cost-effective replacement for 1/4-inch, 4 mm and 8 mm digital linear tape drives.

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|---|
| Model Name..... | LTO-4 HH SAS Tape Drive |
| Drive Type..... | Imation LTO Ultrium 4 HH SAS tape drive |
| Data Capacity | 800 GB native per cartridge; up to 1.6 TB with 2:1 compression |
| Data Transfer Rate | Up to 120 MB/sec native |
| Data Cartridges..... | •Imation Ultrium LTO 4 Tape Cartridge (with or without case and label) •Imation Ultrium LTO 4 WORM Tape Cartridge (with or without case and label) |
| Cleaning Cartridge..... | Imation Ultrium LTO Universal Cleaning Cartridge |
| Weight | 4.3 kg (9.4 lb) External, 1.6 kg (4 lb) Internal |
| Power Requirements..... | 1.0-0.5 A at 100-240 V AC, 50/60 Hz |
| Dimensions..... | 21.3 cm W x 5.8 cm H x 33.2 cm D - External (8.4 in. x 2.3 in. x 13.1 in.) 14.8 cm W x 4.27 cm H x 21.0 cm D - Internal (6 in W x 2 in H x 8 in D) |
| UPC Code | 051122283581 External, 051122283611 Internal |
| Warranty | 3 years |

| DESCRIPTION | UPC | PRIMARY PACK SIZE (LxWxH) | WEIGHT |
|--|--------------|------------------------------|-----------|
| LTO-4 HH SAS External Tape Drive | 051122283581 | 17.3" x 12.6" x 11.8" | 14.65 lbs |