



LTO-3 HH

High-Performance Data Protection
in a simple and affordable half-
height form factor

Quantum's LTO-3 half-height tape drive provides excellent performance while offering up to 400GB of native capacity. Its simple half-height form factor and SCSI or SAS interface option allow easy installation and integration into your data center. The LTO-3 HH tape drive is backward read and write compatible with LTO-2 media and backward read compatible with LTO-1 media.

Quantum's FastSense™ feature maximizes the transfer rates of the LTO-3 HH tape drives by using a multiple-speed sensor that matches the speed at which the drive is streaming data to optimize the backup cycle. This helps prevent the "back-hitching" that slows down many tape drives if the computer system cannot transfer data fast enough. In addition, Quantum adds features like SmartVerify™ to concurrently verify all data written to the tape, virtually eliminating the time-consuming verify pass during backup operations. And, an advanced cooling design helps provide extended tape life.

The LTO-3 HH is available in a server-installable internal, convenient tabletop or space-efficient rackmount configuration. Quantum "Backup Ready" certified solutions allow you to go from box-to-backup in minutes with the highly reliable Quantum LTO-3 HH tape drive and durable Quantum media.

TAPE DRIVE

UP TO 800GB CAPACITY (2:1
COMPRESSION)

UP TO 432GB/HR TRANSFER RATE (2:1)

"BACKUP READY" SOLUTION

3-YEAR RAPID EXCHANGE WARRANTY

FEATURES AND BENEFITS

- **Superior Performance** – LTO-3 HH reaches native transfer speeds of up to 216GB/hr
- **Complete Solution** – Tape drive plus data and cleaning cartridges
- **Reliability You Can Trust** – Enhancement features like SmartVerify and Dynamic PowerDown™
- **Compatibility** – Previous generation media read and write capabilities
- **LTO WORM (Write Once, Read Many)** – Addresses regulatory and compliance requirements
- Available in Ultra 320 SCSI or 3GB/s SAS

DRIVE CAPACITY AND PERFORMANCE

Drive Type	Interface	Cartridge Capacity Native/Compressed (GB)	Drive Throughput Native/Compressed (MB/sec)	Average File Access Time (sec)
LTO-3 HH	3 GB/sec SAS	400 / 800	60 / 120	70
LTO-3 HH	Ultra 320 SCSI	400 / 800	60 / 120	70

Configurations: Internal Bare, Internal Kit, Tabletop Kit and 1U Rackmount

Interface Connector Type

3 GB/s SAS: SFF8482 (Internal), SFF8088 (Tabletop and Rack)
Ultra 320 SCSI: HD68 LVDS

Burst Transfer Rate (MB/sec)

SAS (max): 300
SCSI (max): 320

Data Rate Matching Range: 20 to 60MB/sec native

Data Buffer Size: 64MB

TAPE/FORMAT COMPATIBILITY

LTO-3 (read/write): 400GB native capacity
LTO-3 WORM (read/write): 400GB native capacity
LTO-2 (read/write): 200GB native capacity
LTO-1 (read only): 100GB native capacity

RELIABILITY

MTBF (hours): 250,000 @ 100% duty cycle
Load/Unload Life: 50,000 cycles
Non-recoverable Error Rate: 1×10^{17} bits (non-media error, clean drive)

PHYSICAL SPECIFICATIONS

Form Factor	Internal w/o bezel	Internal w/ bezel	Tabletop	1U Rackmount
Width (in/mm)	5.75 / 146.1	5.88 / 149.3	8.8 / 223	19.0 / 483
Height (in/mm)	1.63 / 41.5	1.69 / 42.9	2.9 / 73.0	1.75 / 44.4
Length (in/mm)	8.11 / 206	8.3 / 211	11.7 / 295	25.25 / 641
Weight (lbs/kg)	3.1 / 1.4	3.2 / 1.45	10.3 / 4.7	20.0 / 9.1

ENVIRONMENTAL

OPERATING

Temperature °F (°C): 50° to 104° (10° to 40°) @ 5 CFM
Humidity: 20% to 80% (non-condensing)
Altitude (maximum): 13,000 ft (4,000 m)

NON-OPERATING

Temperature °F (°C): -40° to 150° (-40° to 66°) excluding media
Humidity: 10% to 95% (non-condensing)

VOLTAGE (V): +5VDC, +12VDC (internal); 100-240 VAC 50/60 Hz (external)

POWER CONSUMPTION

Idle: 13 Watts
Typical: 23 Watts
Peak: 31 Watts

TAPE FORMAT SPECIFICATIONS

Recording Format: LTO Ultrium 3
Recording Density: 9.64KB/mm
Encoding Method: 16 Channel PRML
Data Compression: ALDC

COMPATIBILITY

Operating Systems: Microsoft Windows, Sun Solaris, Red Hat Linux, SuSE Linux
Software/Hardware: Go to www.quantum.com for the most up-to-date tested solutions

TAPE SPECIFICATIONS

Cartridge Dimensions (L×W×H): 4" × 4.15" × .85"
(102mm × 105.4mm × 21.5mm)
Archive Storage: 30 years
Durability: 20,000 load/unload cycles

WARRANTY

Tape: Limited lifetime
Tape Drive: 3 years limited with Rapid Exchange

Model Numbers and Descriptions

TC-L32AX-BR-B LTO-3 HH, Internal Bare, SCSI, black bezel
TC-L32AX-EY-B LTO-3 HH, Internal Kit, SCSI, black bezel
TC-L32BX-EY-B LTO-3 HH, Tabletop Kit, SCSI, black
TC-L33CX-EY-B LTO-3 HH, 1U Rackmount, SCSI, black

TC-L32AN-BR-B LTO-3 HH, Internal Bare, SAS, black bezel
TC-L32AN-EY-B LTO-3 HH, Internal Kit, SAS, black bezel
TC-L32BN-EY-B LTO-3 HH, Tabletop Kit, SAS, black
TC-L33CN-EY-B LTO-3 HH, 1U Rackmount, SAS, black

For contact and product information,
visit quantum.com or call 866-809-5230

Quantum
BE CERTAIN™

©2012 Quantum Corporation. All rights reserved. Quantum, the Quantum logo, DXi, Dynamic PowerDown, FastSense, Scalar, SmartVerify and StorNext are either registered trademarks or trademarks of Quantum Corporation and its affiliates in the United States and/or other countries. Linear Tape-Open, LTO, the LTO Logo, Ultrium and the Ultrium Logo are registered trademarks of HP, IBM and Quantum in the US and other countries. All other trademarks are the property of their respective owners.

About Quantum

Quantum Corp. (NYSE:QTM) is a proven global expert in data protection and Big Data management that provides a unique combination of intelligent storage solutions and unmatched value for traditional, virtual and cloud environments. From small businesses to multinational enterprises, more than 50,000 customers trust Quantum to help cost-effectively manage data growth and extract the full value from their digital assets. Quantum's offerings include: DXi®-Series disk-based deduplication and replication systems for fast backup and restore, vmPRO solutions for protecting virtual machine data, Scalar® tape automation products for disaster recovery and long-term data retention, and StorNext® Big Data management software and appliances for high-performance file sharing and archiving.