

Reliable 24-inch printer for small workgroups









Do more in less time—easy setup, easy sharing

- · Easily meet deadlines, even when they are unexpected. At up to 35 seconds per D/A1 page, you can print CAD/GIS projects up to 3 times faster than with the HP Designjet 500 Printer.(1
- Small teams can share this printer thanks to its built-in network card.
- Print batch HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, PowerPoint) files easily—without opening any application—thanks to the free HP Instant Printing Utility.
- Handle prints right off the printer—fast-drying HP Vivera inks produce smudge-resistant
- Intelligent technology, built into Original HP supplies and the printer, provides time-saving features.

Small details increase your power to communicate

- Achieve rich, dark blacks and fine detailed lines with HP Vivera inks, including 2 HP Vivera blacks and a gray ink in this 6-ink printing system.
- Produce exacting detail with 0.0008 inch (0.02 mm) minimum line width, (2 and highly accurate drawings with 0.1% line accuracy.

- Easily create stunning large-format posters that convey your message loud and clear with the optional Serif PosterDesigner Pro for HP.(3
- Transform your everyday printing with 2 HP media innovations—new and improved HP bond papers with ColorPRO Technology and HP Recycled Bond Paper, made of 100% recycled base paper.

Focus on your design with a reliable printer

- Work with confidence knowing this printer has 2 GB of dedicated memory intended exclusively for faster processing of even the most complex files.
- Experience greater operating system support with original HP-GL/2 and RTL.
- Upgrade with peace of mind knowing you will be able to reproduce the color of your previous Designjet.

COHIGHLIGHTS HP DESIGNJET T620 PRINTER

- Save paper with blank print area detection, image auto-rotate and realistic print previews
 Less ink wasted thanks to efficient installation and maintenance routines
- Free, convenient cartridge and printhead recycling[®] Supports 100% recycled HP media ENERGY STAR® Qualified Product

















Compared to the HP Designjet 500 Plus Printer series, based on 4 copies of 50 D pages using normal print quality on plain paper. Intervention time not included.

Serif PosterDesigner Pro for HP is an optional software accessory to be purchased separately

HP DESIGNJET T620

PRINTER SERIES

TECHNICAL SPECIFICATIONS

Print Speed(1 Line drawings(2	Fast: 35 sec/page on D/A1, 72 D/A1 prints per hour
Color images	Fast: 364 ft²/hr (34 m²/hr) 3
Color inages	Best: 26 ft²/hr (2.4 m²/hr)/ ⁴
Printing	5631. 20 11 / 111 (2.4 111 / 111)
Print resolution	Up to 2400 x 1200 optimized dpi
Margins	Roll: 0.2 x 0.2 x 0.2 x 0.2 in (5 x 5 x 5 x 5 mm)
(top x bottom x left x right)	Sheet: 0.2 x 0.67 x 0.2 x 0.2 in (5 x 16.75 x 5 x 5 mm)
Technology	HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
Ink colors	Cyan, gray, magenta, matte black, photo black, yellow
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Ink cartridge size	130 ml (cyan, gray, magenta, matte black, photo black, yellow)
iiik cairiiage 3126	69 ml (cyan, gray, magenta, photo black, yellow)
Printheads	3 (matte black and yellow, magenta and cyan, gray and photo black)
Line accuracy	+/- 0.1% ⁵
Minimum line width	0.0008 in (0.02 mm) (HP-GL/2 addressable)
Guaranteed minimum line width	0.0024 in (0.06 mm) (ISO/IEC 13660:2001(E)) ⁶
Maximum print length	300 ft (91 m) (OS and application dependent)
Media	300 ii (41 iii) (O3 diid applicalion dependeni)
	Shoot food, well food, automatic autor
Handling Types	Sheet feed; roll feed; automatic cutter Bond and coated papers, technical papers, films, photographic papers, backlit
Types	materials, self-adhesive materials
Weight	60 to 328 g/m ²
vveignt Size	8.26 x 11 to 24 x 66 in (210 x 279 to 610 x 1676 mm) sheets; 11 to 24 in (27.94 to
3126	6.26 x 1 1 to 24 x 66 in (210 x 2/9 to 610 x 16/6 mm) sneets; 11 to 24 in (2/.94 to 60.96 cm) rolls
Thickness	Up to 31.5 mil
Memory	Op 10 0 1.5 (IIII
Melliory	2 GB dedicated file-processing memory ⁽⁷⁾
Connectivity	2 OB accided me-processing memory:
	1 Fast Ethernet (100Base-T) port, 1 Hi-Speed USB 2.0 certified port, 1 EIO Jetdirect
Interfaces (standard)	accessory slot
Interfaces (optional)	HP Jetdirect EIO print servers
Print languages (standard)	HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Drivers (included)	HP-GL/2, HP-RTL drivers for Windows® (optimized for AutoCAD 2000 and higher);
Differs (included)	HP PCL 3 GUI driver for Mac OS X; support for Citrix XenApp and Citrix XenServer
	environments
Recommended system requirements	
Мас	Mac OS X v 10.4, Mac OS X v 10.5: PowerPC G4, G5, or Intel Core Processor; 1 G
	RAM; 2 GB available hard disk space
Windows	Windows XP® (SP2 or later): Intel® Pentium® family or AMD® K6/Athlon/Duron family
	(1 GHz), 1 GB RAM, 2 GB available hard disk space; Windows Vista®: 32-bit (x86) or
	64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	
Printer	49.7 x 27.2 x 41.2 in (1262 x 690 x 1047 mm)
Shipping	56.69 x 30.16 x 30.4 in (1440 x 766 x 763 mm)
Weight	
Printer	143 lb (65 kg)
Shipping	224 lb (102 kg)
Mank's in the same	
what's in the box	
whar's in the box	
ventar's in the box	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software,
Environmental ranges	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord
Environmental ranges Operating temperature	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C)
Environmental ranges Operating temperature Recommended operating	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord
Environmental ranges Operating temperature Recommended operating temperature	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (-25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 b(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz),
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Maximum Power consumption Maximum Power requirements	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts -2.9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, active Sound power, and by Power consumption Maximum Powersave Off Power requirements Certification Safety	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST, Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, active Sound power, and by Power consumption Maximum Powersave Off Power requirements Certification Safety	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST, Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, active Sound power, and by Power consumption Maximum Powersave Off Power requirements Certification Safety	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified o
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, atandby Sound power, active Sound power, and the Sound power on sumption Maximum Powers are on sumption Maximum Power requirements Certification Safety Electromagnetic	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified of Class A product: Korea (KCC)
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, active Sound power, active Sound power active Sound pressure, standby Fower requirements Certification Safety Electromagnetic	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts -2.9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST, Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified or Class A product: Karea (KCC) WEEE, EU RoHS, China RoHS, REACH, EUP, FEMP
Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power power on the sound power on sumption Maximum Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up software, power cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified of Class A product: Korea (KCC)
Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up softwower cord 41 to 104° F (5 to 40° C) 59 to 95° F (15 to 35° C) (depending on paper type) -13 to 131° F (25 to 55° C) 0 to 80% RH (depending on paper type) 0 to 95% RH 57 dB(A) 29 dB(A) 6.9 B(A) 4.4 B(A) 120 watts < 9.5 watts (< 27.5 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz) 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russ Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (CCS), Class A product: Korea (KCC)

ORDERING INFORMATION

	INICKMATION
Product	
CK835A	HP Designjet T620 24-in Printer
Accessories	
Q6700A	HP Designjet Zxx00/T1xx0/T6x0 24-in Spindle
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server
CN088A Serif PosterDesigner Pro for HP	
Original HP pri	
C9380A	HP 72 Gray and Photo Black Printhead
C9383A	HP 72 Magenta and Cyan Printhead
C9384A	HP 72 Matte Black and Yellow Printhead
Original HP ink	
C9397A	HP 72 69-ml Photo Black Ink Cartridge
C9398A	HP 72 69-ml Cyan Ink Cartridge
C9399A	HP 72 69-ml Magenta Ink Cartridge
C9400A	HP 72 69-ml Yellow Ink Cartridge
C9401A	HP 72 69-ml Gray Ink Cartridge
C9403A	HP 72 130-ml Matte Black Ink Cartridge
C9370A	HP 72 130-ml Photo Black Ink Cartridge
C9371A	HP 72 130-ml Cyan Ink Cartridge
C9372A	HP 72 130-ml Magenta Ink Cartridge
C9373A C9374A	HP 72 130-ml Yellow Ink Cartridge
	HP 72 130-ml Gray Ink Cartridge
Original HP pri	
Q6627A	HP Super Heavyweight Plus Matte Paper 210 g/m², 36 in x 100 ft/914 mm x 30,5 m
Q6628A C6030C	HP Super Heavyweight Plus Matte Paper 210 g/m², 42 in x 100 ft/1067 mm x 30,5 m HP Heavyweight Coated Paper 130 g/m², 36 in x 100 ft/914 mm x 30,5 m
C6569C	
Q1956A	HP Heavyweight Coated Paper 130 g/m², 42 in x 100 ft/1067 mm x 30,5 m
C6019B	HP Heavyweight Coated Paper 130 g/m², 42 in x 225 ft/1067 mm x 67,5 m
C6020B	HP Coated Paper 90 g/m², 24 in x 150 ft/610 mm x 45,7 m HP Coated Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m
C6980A	HP Coated Paper 90 g/m², 36 in x 300 ft/914 mm x 91,4 m
C1860A	HP Bright White Inkjet Paper 90 g/m², 24 in x 150 ft/610 mm x 45,7 m now with ColorPRO Technology
C1861A	HP Bright White Inkjet Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology
C6810A	HP Bright White Inkjet Paper 90 g/m², 36 in x 300 ft/914 mm x 91,4 m now with ColorPRO Technology
Q1397A	HP Universal Bond Paper 80 g/m², 36 in x 150 ft/914 mm x 45,7 m now with ColorPRO Technology
C3868A	HP Natural Tracing Paper 90 g/m², 36 in x 150 ft/914 mm x 45,7 m
C3875A	HP Clear Film 174 g/m², 36 in x 75 ft/914 mm x 22,9 m
51642B	HP Matte Film 160 g/m², 36 in x 125 ft/914 mm x 38,1 m
Q1427A	HP Universal High-gloss Photo Paper 190 g/m², 36 in x 100 ft/914 mm x 30,5 m
Q1421 A	HP Universal Semi-gloss Photo Paper 190 g/m², 36 in x 100 ft/914 mm x 30,5 m
CG459A	HP Premium Matte Photo Paper 210 g/m², 24 in x 100 ft/610 mm x 30,5 m
CG460A	HP Premium Matte Photo Paper 210 g/m², 36 in x 100 ft/914 mm x 30,5 m
C7960A	HP Reverse Print Matte Backlit Film 160 g/m², 36 in x 75 ft/914 mm x 22,9 m
Q8834A	HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in x 75 ft/914 mm x 22,9 m
CG886A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in x 100 ft/610 mm x 30,5 m
CG887A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in x 100 ft/914 mm x 30,5 m
CG888A	HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in x 100 ft/1067 mm x 30,5 m
CG883A	HP Cockle-free Coated Paper 100 g/m², 24 in x 150 ft/610 mm x 45,7 m
CG884A	HP Cockle-free Coated Paper 100 g/m², 36 in x 150 ft/914 mm x 45,7 m
CG885A	HP Cockle-free Coated Paper 100 g/m², 42 in x 150 ft/1067 mm x 45,7 m
CG889A	HP Recycled Bond Paper 80 g/m², 24 in x 150 ft/610 mm x 45,7 m made of 100% recycled base paper
CG890A	HP Recycled Bond Paper 80 g/m², 36 in x 150 ft/914 mm x 45,7 m made of 100% recycled base paper
CG891A	HP Recycled Bond Paper 80 g/m², 42 in x 150 ft/1067 mm x 45,7 m made of 100% recycled base paper
HP Care Pack Services	
US263E	HP 3-year Next Business Day Onsite Support
H4518E	HP Installation Services with Network Setup
US260E	HP 3-year Same Day Onsite Service (9x5)
US256E	HP 3-year Same Day Onsite Service (13x5)
US262E	HP 4-year Next Business Day Onsite Support
US 261 E	HP 5-year Next Business Day Onsite Support

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/designjet/supplies

- Mechanical printing time
 Printed on plain media with Economode on
 Printed on coated media
 Printed on coated media
 Printed on glossy media
 Printed on glossy media
 +/-0.1% of the specified vector length or +/-0.1 mm (whichever greater) at 73° F (23° C), 50-60% relative humidity, on E/A0 printing material in Best or Normal mode with HP Matte Film
 Measured on HP Matte Film
- 7) 384 MB RAM memory

FOR MORE INFORMATION, VISIT OUR WEBSITE AT

WWW.HP.COM/GO/DESIGNJETT620

One-year limited hardware warranty

© Copyright 2009 Hewlett-Packard Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AMD is a trademark of Advanced Micro Devices, Inc. Intel and Pentium are trademarks of Intel Corporation in the U.S. and other countries. Windows, Windows XP, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

